

Laminating ID CARD PRINTER

SMART-51L













Single or Dual Sided Laminating ID Card Printer

- Patented 8-Second Heat Up Time
- Fast, Quiet with User Friendly LCD
- FINE™ Imaging Technology
- **Lowest Cost per Print**
- **3 YEAR WARRANTY**

Department of Transportation - Federal Aviation Administration

QUALITY AIRLINES

Jason Roberts

Date of Issue - 01/01/2017



AIRLINES XERCISE THE PRIVILEGES OF LTI-ENGINE LAND INSTRUMENT MERICIAL JETLINERS.



Increase Card Life, Increase Security, Decrease Costs

IDP's SMART-51L printer produces high quality printed and laminated cards for government credentials, student photo identification, and secured access control badges.

Ideally suited for today's increased security on identification cards, the SMART-51L with patented Direct Lamination™ technology provides an ultra-fast laminating solution with state-of-the-art security features. When it comes to security and reliability, the SMART-51L provides premium protection.



- Single or Dual Sided Printing & Laminating
- 8 Second Heat Up Time with Patented Direct Lamination™
- Printing & Laminating Speed: Max. 22 sec/card (YMCK & Single Lamination)
- 300dpi (color), 600, 1200dpi (mono only)
- Edge to Edge Printing
- 51S & 51D Field Upgradable to 51L
- 2 Lines LCD with 2 LED Buttons for Front Operation
- Holographic Lamination for Visual Security & Card Durability
- Installable Encoders: MS, Contact & Contactless
- Upgradable Ethernet

Requires High Security ID Cards

National ID Cards Government & Military ID Cards High Security Access Control ID Cards Law Enforcement & Correctional Facility ID Cards **Driver Licenses** Airport ID Cards





SMART IDesigner ensures accurate card issuance and data management with your SMART series of printers. This application offers simple design tools to allow the user to create a truly customized card within minutes. SMART IDesigner offers advanced user tools such as database connections, camera and signature scanners plugin support, as well as smart card reading and encoding.

- Design and print (Image, Photo and Text)
- Auto portrait (Auto face detection, adjustment of size
- Printing of sequential numbersCard design templates
- Plug-in for supporting external devices (Sign pad, Camera, Scanner)
- Magnetic stripe (MS), contact & contactless smart card encoding by using plug-in program



The SMART series printers come with highly effective and tested physical and electronic security features.

- PASSWORD verification with administrator and user
- PC AUTHENTICATION locks the SMART printer to a
- DATA ENCRYPTION over USB and SSL (secure socket
- HYSICAL LOCKS are standard on the SMART-70 and an optional feature on the SMART-51 Series
- Ethernet SNMPv3



The SMART series offers "single-wire" printing and encoding.

- -The SMART Ethernet module can not only print over your network, but can also be configured to encode magnetic stripes, contact IC chips and contactless smart cards over
- The SMART Ethernet module can be configured to accept "open card protocol" print commands for direct printing without a driver

Specifications

SMART-**51**L

 Print Type Dye-Sublimation Print Area Edge to Edge

 Resolution 300dpi (color), 600, 1200dpi (mono only)

 Dual Sided Printing **Dual Sided Printing**

Card Feeding Automatic

Card Size ISO CR80 or ISO CR79 (Option-Factory Installed)

Card Thickness 0.38mm (15mil), 0.76mm (30mil)

 Card Type PVC, PET, Composite PVC

5 sec./card (720 cards/hour) Monochrome Max. 17 sec./card (212 cards/hour) YMCKO Max. 22 sec./card (164 cards/hour) YMCKOK

100 Cards / 200 Cards with cover open Input Hopper

 Output Hopper Front: 40 cards / Rear: 100 Cards

*Optional Rear-Side Stacker

Mode • Film (clear & holographic)

Speed I Simultaneous (Single Lamination)

> One by One (Single Lamination)

Single & Dual 0.6mil, 1.0mil

22 sec./card (YMCK), 32 sec./card (YMCKK)

43 sec./card (YMCK), 53 sec./card (YMCKK)

Memory 64MB RAM (additional 4GB with gender board) Display 2 Line LCD

 Control Panel 2 LED Buttons

Microsoft Windows 7/8/10. Mac OS. Linux Supported Platforms

 Communication USB, Ethernet-SNMPv3 (Option),

Wifi Kit (Option)

 Power Supply Free Voltage (AC100/200V, 50~60Hz)

 Power Consumption 96W

 Temperature/Humidity 15~35ºC/35~70%

 Millimeter (WxLxH) 165 x 675 x 210 6.5 x26.6 x 8.3 Inch (WxLxH)

8.8/19.4 Kg/lbs

 Magnetic ISO7811 (Track I, II, III Read/Write, HiCo/LoCo), JIS II

Contact ISO 7816 (ID-1)

MIFARE, ISO 14443 (Type A/B), ISO 15693 Contactless

DESFIRE, iCLASS



Consumables

659366 YMCKO

Full Color Ribbon with Resin Black & Overlay

250 Cards/Roll

659376 YMCKOK

Full Color Ribbon with Resin Black & Overlay & Black for Back Side

200 Cards/Roll

Full Color Ribbon with UV Panel, Resin Black and Overlay

659380



200 Cards/Roll

659378 **HYMCKO**

Half Panel Size Color Ribbon with Resin Black and Overlay





Holographic

COLOR RIBBONS

Designs



Specifications and availability may change without notice.

Part Numbers:

SMART-51L 651400 SMART-51LN (Eth) 651410 Contactless Enc. (USB) 651360 Contactless Enc. (Eth) 651362 Contact IC Enc. 651359 Mag Encoding 651356 Clear Lam., 250/Cards 659390 659392 Holo. Lam., 250/Cards

Add "K" to any printer part number for a kit (1 YMCKO Ribbon, 1-100pk Cards, & 1 Long Cleaning Card)

IDP Americas, Inc. 1485 South County Trail - Unit 306,

TEL: +82-2-6099-3700

FAX: +82-2-6099-3717 E-MAIL: sales@idp-corp.com

IDP Corp., Ltd.

East Greenwich, RI 02818 TEL +1.401.400.7111 FAX +1.401.667.7445 E-MAIL sales.na@idp-corp.com

OFFICE: Room 601m 50, Digital-ro 33-gil, Guro-gu,

Seoul, 152-742, Korea

www.idp-corp.com